

Flight Light Inc. 2708 47th Ave. Sacramento, California, U.S.A. 95822-3806



PH (916) 394-2800 TF (800) 806-3548 FX (916) 394-2809 EM info@flightlight.com

Airport / Heliport Nylon Windsocks & Frames

Nylon Windsocks

The long-lasting, international orange nylon cloth is treated with a water repellent and UV inhibitor. The colorfast nylon is lightweight, responsive to the slightest wind, resists mildew, and won't crack or peel. Every seam is double-stitched with weather-resistant nylon thread. A 400 lb. tensile strength webbing is added in the throat for reinforcement. Brass grommets are evenly spaced allowing for the standard lace-on or tie wrap method of attachment. Tie wraps are provided with every order.

Features

- Long-lasting 6.2 oz. colorfast nylon (will not fade as fast as poly coated vinyl)
- · Weather-resistant nylon thread
- 400 lb. tensile strength webbing
- High quality brass grommets
- Water repellent
- Meets or exceeds AC 150/5345-27D

Ordering Codes

Windsock Size Product Code (throat X length)

I Touuci Coue	(till oat A length)
WS-AS-	624: 6" X 24"
	840: 8" X 40"
	930: 9" X 30"
	1036: 10" X 36"
	1248: 12" X 48"
	1356: 13" X 56"
	1848: 18" X 48"
	1860: 18" X 60"
	1872: 18" X 72"
	1896: 18" X 96"
	2096: 20" X 96"
	2496: 24" X 96"
	2896: 28" X 96"
	3612: 36" X 12'

Frame sold separately.



Machined Bearing Windsock Frame

These frames are one of our most popular among aviation enthusiasts as well as general aviation professionals. Manufactured from 1/4" cold rolled steel and designed for many years of service. The frames are zinc plated for a long-lasting, chrome-like finish. A machined bearing is added that allows the windsock to respond to the slightest wind. All you need for installation is a 1/2" collar looking up from your mast. Three frame diameters available: 6", 10", and 13".





Economy Windsock Frame

This zinc-plated frame is a favorite for the aviation enthusiast. Just slip it over a 3/4" rod or water pipe, with a shaft collar underneath and on top of the frame, and you are ready to go. Frame diameter: 10".

Visit our web site: www.flightlight.com

Data Sheet: Windsocks & Frames 4/9/2019



Flight Light Inc. 2708 47th Ave. Sacramento, California, U.S.A. 95822-3806



PH (916) 394-2800 TF (800) 806-3548 FX (916) 394-2809 EM info@flightlight.com Airport / Heliport Nylon Windsocks & Frames

Double Ball Bearing Windsock Frame

This frame design is truly a mainstay for general aviation. The strong, sturdy, double ball-bearing and 1/4" cold rolled steel design will offer you many years of exceptional service. Having a 3/4" collar, or female thread looking up, allows you to simply screw the extension rod into the awaiting threads for easy installation. The frame features a black powder coat finish for added durability. Three frame diameters are available: 18", 24", and 36".



Double Ball Bearing Extended Windsock Frame

This frame features an extension, projecting approximately 28" into the windsock, that holds the windsock throat open and ready. The strong, sturdy, double ball-bearing and 1/4" cold rolled steel design will offer you many years of exceptional service. Having a 3/4" collar, or female thread looking up, allows you to simply screw the extension rod into the awaiting threads for easy installation. The frame features a black powder coat finish for added durability. Three frame diameters are available: 18", 24", and 36".



Visit our web site: www.flightlight.com

Data Sheet: Windsocks & Frames 4/9/2019